



## SERVICE JACKS

- A built-in by-pass device protects hydraulic system from over pumping damage, U.S. Patent No.5,946,912
- Metered release system allows for precise load control
- Largest saddle in category
- Extra wide wheels and solid stance designed for stability under load stress

**FAST & SAFE!**  
Convenient foot pedal  
designed for fast, no load lifts  
U.S. Patent No. 5,431,369



**21025**  
2-1/2 Ton Capacity



**21030**  
3 Ton Capacity

| Model | Capacity  | Minimum Height | Maximum Height | Handle Length | Saddle Diameter | Jack Size Length | Jack Size Width | Jack Size Height | G.W.    |
|-------|-----------|----------------|----------------|---------------|-----------------|------------------|-----------------|------------------|---------|
| 21025 | 2-1/2 Ton | 5"             | 19-1/2"        | 42-1/8"       | 5"              | 25-3/8"          | 13-1/8"         | 6-1/2"           | 73 Lbs. |
| 21030 | 3 Ton     | 5-1/4"         | 19"            |               |                 | 27-1/2"          | 13-3/8"         | 6-3/8"           | 87 Lbs. |

## LONG CHASSIS SERVICE JACKS

- Handle actuated release valve provides metered control at any desired lowering speed
- Wide stance and low center of gravity provides optimum stability under load stress
- Heavy gauge, steel frame helps prevent distortion and twisting
- A built-in by-pass device protects hydraulic system from over pumping damage, U.S. Patent No.5,946,912

**FAST & SAFE!**  
Convenient foot pedal  
designed for fast ,  
no load lifts.



**22050C**  
5 Ton Capacity



**22100C**  
10 Ton Capacity

| Model  | Capacity | Minimum Height | Maximum Height | Handle Length | Saddle Diameter | Jack Size Length | Jack Size Width | Jack Size Height | G.W.     |
|--------|----------|----------------|----------------|---------------|-----------------|------------------|-----------------|------------------|----------|
| 22040C | 4 Ton    | 5"             | 24"            | 42-5/8"       | 5-1/2"          | 50-5/8"          | 15-3/8"         | 7-1/2"           | 156 Lbs. |
| 22050C | 5 Ton    | 7"             | 27"            |               | 6-1/2"          | 57-3/4"          | 17"             | 7-5/8"           | 233 Lbs. |
| 22100C | 10 Ton   |                |                |               | 7-3/8"          | 54-3/4"          | 20"             | 12-3/4"          | 427 Lbs. |